

tesa® 4124

Premium general purpose carton sealing tape

PRODUCT INFORMATION

Product Description

tesa® 4124 is a premium packaging tape based on a PVC-film backing and a natural rubber adhesive. It shows excellent performance on all kind of cardboards and secures a safe closure of medium and also heavy-weight cartons. tesa® 4124 unwinds smoothly and without noise which makes 4124 ideal for use in hand dispensers and automatic sealing equipment.

The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Main Application

tesa® 4124 is used for manual and automatic sealing of cartons of medium to heavy-range weight.

Technical Data

■ Backing material	PVC film	■ Adhesion to steel	3.2 N/cm
■ Total thickness	65 µm	■ Elongation at break	60 %
■ Type of adhesive	natural rubber	■ Tensile strength	60 N/cm

Properties

■ Automatic application	yes	■ Printability	++
■ Manual application	yes	■ Low noise unwinding	yes

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesa® 4124 is easy printable. Available colours: white, havana and transparent

For latest information on this product please visit <http://l.tesa.com/?ip=04124>

Page 1 of 1 / As of 05/06/15

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.