

Description

This single-sided tape consists of a PVC carrier coated with natural rubber adhesive. The adhesive provides immediate adhesion and good adhesion power on different surfaces.

Carrier

PVC film (30 micron, transparent, blue, green or red)

Adhesive

Natural rubber (white)

Area of use

This tape is suitable as edge sealing tape for mounting photopolymer- or rubber printing plates in flexographic printing.

Technical Data

Thickness* (carrier + adhesive)	55 micron	
Temperature resistance***	up to +70° C	
Resistance to solvents and chemicals	with expert application resistant to weak acids, salts and alkalis	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	3 N/25 mm	after 1 min
	4 N/25 mm	after 20 min
	5 N/25 mm	after 24 h
Tensile strength* (DIN EN ISO 527)	100 N/25 mm	
Shelf life**	1 years	
Application temperature	> +15° C	

* average

** in original packaging, at 20° C and 50% relative humidity

*** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.